

# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Trade name**

Oil Lacquer

**Product no.**

-

**REACH registration number**

Not applicable

**Other means of identification**

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

wood surfaces, indoors

**Uses advised against**

-

The full text of any mentioned and identified use categories are given in section 16

### 1.3. Details of the supplier of the safety data sheet

**Company and address**

WoodCare Denmark A/S

Tvæervej 6

6640 Lunderskov

Denmark

Tel: 99585600

Fax: 99585634

**Contact person**

LFH

**E-mail**

info@ttwoodcare.com

**SDS date**

06-11-2013

**SDS Version**

1.0

### 1.4. Emergency telephone number

Use your national or local emergency number

See section 4 "First aid measures"

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Flam. Liq. 3 // EUH066, H336, H226

See full text of H/R-phrases in section 2.2.

**DPD/DSD Classification**

-

Vapours may cause drowsiness and dizziness.(R67). Repeated exposure may cause skin dryness or cracking.(R66). Flammable.(R10).

### 2.2. Label elements

**Hazard pictogram(s)**



**Signal word**

Warning!

**Hazard statement(s)**

Flammable liquid and vapour. (H226)  
 May cause drowsiness or dizziness. (H336)

**Identity of the substances primarily responsible for the major health hazards**

-

<b>Safety statement(s)</b>	<b>General</b>	If medical advice is needed, have product container or label at hand. (P101) Keep out of reach of children. (P102)
	<b>Prevention</b>	Keep away from heat/sparks/open flames/hot surfaces. — No smoking. (P210)
	<b>Response</b>	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. (P303+P361+P353)
	<b>Storage</b>	Store in a well-ventilated place. Keep cool. (P403+P235)
	<b>Disposal</b>	Dispose of contents/container to an approved waste disposal plant. (P501)

**2.3. Other hazards**

Contains drying oils. Risk of self-ignition. After spills and used cloths, etc. have been recovered, store in fireproof waste disposal containers before destroying. This product contains teratogenic substances, which can cause long-term damage to the human embryo.

The product contains substances that can damage the reproductive system.

This product contains an organic solvent. Repeated exposure to organic solvents can result in damage to the nervous system and inner organs, such as the liver and kidneys.

**Additional labelling**

Contains cobalt bis(2-ethylhexanoate). May produce an allergic reaction. Repeated exposure may cause skin dryness or cracking. (EUH066)

**Additional warnings**

-

**VOC**

VOC-MAX: 500 g/l, MAXIMUM VOC CONTENT (A (SB)): 500 g/l.

**SECTION 3: Composition/information on ingredients**

**3.1/3.2. Substances**

NAME:	Naphtha (petroleum), hydrotreated heavy
IDENTIFICATION NOS.:	CAS-no: 64742-48-9 EC-no: 265-150-3 Index-no: 649-327-00-6
CONTENT:	25-40%
DSD CLASSIFICATION:	R10 Xn;R65 R66
CLP CLASSIFICATION:	Flam. Liq. 3, Asp. Tox. 1 H226, H304, EUH066
NOTE:	S
NAME:	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclic, <2% aromatics
IDENTIFICATION NOS.:	REACH-no: 01-2119463258-33
CONTENT:	15-25%
DSD CLASSIFICATION:	R10 Xn;R65 R67 R66
CLP CLASSIFICATION:	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1 H226, H304, H336, EUH066
NOTE:	S
NAME:	Naphtha (petroleum), hydrotreated heavy
IDENTIFICATION NOS.:	CAS-no: 64742-48-9 EC-no: 265-150-3 Index-no: 649-327-00-6
CONTENT:	1-5%
DSD CLASSIFICATION:	Xn;R65 R66
CLP CLASSIFICATION:	Asp. Tox. 1 H304, EUH066
NOTE:	S

According to EC-Regulation 1907/2006 (REACH)

NAME:	2-butoxyethanol
IDENTIFICATION NOS.:	CAS-no: 111-76-2 EC-no: 203-905-0 Index-no: 603-014-00-0
CONTENT:	1-5%
DSD CLASSIFICATION:	Xn; R20/21/22 Xi; R36/38
CLP CLASSIFICATION:	Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2 H302, H312, H315, H319, H332
NOTE:	S
NAME:	Naphtha (petroleum), hydrotreated heavy
IDENTIFICATION NOS.:	REACH-no: 01-2119457273-39
CONTENT:	1-5%
DSD CLASSIFICATION:	Xn;R65 R66
CLP CLASSIFICATION:	Asp. Tox. 1 H304, EUH066
NOTE:	S
NAME:	cobalt bis(2-ethylhexanoate)
IDENTIFICATION NOS.:	CAS-no: 136-52-7 EC-no: 205-250-6 REACH-no: 01-2119524678-29
CONTENT:	<1%
DSD CLASSIFICATION:	Xi;R43 Rep3;R62 N;R50/53
CLP CLASSIFICATION:	Eye Irrit. 2, Skin Sens. 1, Rep. 2, Aquatic Acute 1, Aquatic Chronic 1 H317, H319, H361, H400, H410

(\*) See full text of H/R-phrases in chapter 16. Occupational limits are listed in section 8, if these are available.  
S = Organic solvent

### Other informations

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor, if in doubt about the injured person's condition or if the symptoms continue. Never give an unconscious person water or similar.

#### Inhalation

Get the person into fresh air and stay with them.

#### Skin contact

Remove contaminated clothing and shoes at once. Skin that has come in contact with the material must be washed thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

#### Eye contact

Remove contact lenses. Flush eyes immediately with plenty of water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. If irritation continues, contact a doctor.

#### Ingestion

Give the person plenty to drink and stay with the person. If the person feels unwell, contact a doctor immediately and take this safety data sheet or the label from the product with you. Do not induce vomiting unless recommended by the doctor. Hold head facing down so that no vomit runs back into the mouth and throat.

#### Burns

Rinse with water until the pain stops and continue for 30 minutes.

### 4.2. Most important symptoms and effects, both acute and delayed

**Reproductive toxicity:** This product contains teratogenic substances which can do long-term damage to human offspring. The effects on the child can be: death, deformity, delayed development, and functional disorders. **Reproductive toxicity:** This product contains substances which can do damage to reproductive capacity, e.g. damage to germ cells or hormonal regulation. The effects can be: sterility, reduced fertility, menstruation disorders, etc. **Neurotoxic effect:** This product contains organic solvents, which can have an effect on the nervous system. Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will then be more prone to absorb dangerous substances, e.g. allergens. **Sensitivity effects:** This product contains substances which can give an allergic reaction on contact with skin. The allergic reaction will typically set in 12-72 hours after exposure as the substance penetrates the skin and reacts with proteins in the outer skin. The body's immune system sees the

chemically changed protein as a foreign body and will try to destroy it.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No special

#### Information to medic

Bring this safety data sheet.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Water jets should not be used, since they can spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, as in the case of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in thick black smoke. Exposure to catabolic products can damage your health. Fire fighters should use proper protection gear. Closed containers, which are exposed to fire, should be cooled with water. Do not let fire-extinguishing water run into sewers and other water courses.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid inhalation of vapours from waste material. Stores that have not ignited must be cooled by water mist. Where possible, remove flammable materials. Make sure there is sufficient ventilation.

#### 6.2. Environmental precautions

No specific requirements.

#### 6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. Cleaning should be done as far as possible using normal cleaning agents. Solvents should be avoided.

#### 6.4. Reference to other sections

See section on "Disposal considerations" with regard to the handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Because of the danger of self-ignition, any waste from the product, spray mist and soiled rags etc. are to be kept in a fire-proof place in air-tight containers, alternatively the waste is to be burned. Smoking, consumption of food or liquid, and storage of tobacco, food or liquids are not allowed in the workrooms. See section on 'Exposure controls/personal protection' for information on personal protection.

#### 7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Must be stored in a cool and ventilated area, away from possible sources of combustion.

#### Storage temperature

Store frost-free.

#### 7.3. Specific end use(s)

This product should only be used for applications described in Section 1.2

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### OEL

2-butoxyethanol (EH40/2005)

Long-term exposure limit (8-hour TWA reference period): 25 ppm | - mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): 50 ppm | - mg/m<sup>3</sup>

Comments: Sk BMGV (Bmgv = Biological Monitoring Guidance Value. Sk = Can be absorbed through skin.)

### DNEL / PNEC

No data available.

### 8.2. Exposure controls

Compliance with the stated exposure limits values should be checked on a regular basis.

#### General recommendations

Smoking, consumption of food or liquid, and storage of tobacco, food or liquid, are not allowed in the workroom.

#### Exposure scenarios

If there is an appendix to this safety data sheet, the indicated exposure scenarios must be complied.

#### Exposure limits

Trade users are covered by the rules of the working environment legislation on maximum concentrations for exposure. See work hygiene threshold values below.

#### Appropriate technical measures

Airborne gas and dust concentrations must be kept as low as possible and below the current threshold values (see below). Use for example an exhaust system if the normal air flow in the work room is not sufficient. Make sure that eyewash and emergency showers are clearly marked.

#### Hygiene measures

Whenever you take a break in using this product and when you have finished using it, all exposed areas of the body must be washed. Always wash hands, forearms and face.

#### Measures to avoid environmental exposure

No specific requirements.

#### Individual protection measures, such as personal protective equipment



#### Generally

Only CE-marked personal protection equipment should be used.

#### Respiratory Equipment

If the ventilation at the work place is not sufficient, use a half or whole mask with an appropriate filter or an air-supplied respiratory protector. The choice depends on the concrete work situation and how long you will be using the product.

#### Skin protection

No specific requirements.

#### Hand protection

Recommended: Nitrile rubber. . Breakthrough time: See the manufacturer's instructions

#### Eye protection

Use face shield. Use safety glasses with a side shield as an alternative.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Form	Colour	Odour	pH	Viscosity	Density (g/cm <sup>3</sup> )
Liquid	Pale yellow	Solvent	-	-	0,9

#### Phase changes

Melting point (°C)	Boiling point (°C)	Vapour pressure (mm Hg)
-	-	-

#### Data on fire and explosion hazards

Flashpoint (°C)	Ignition (°C)	Self ignition (°C)
>40	-	-
Explosion limits (Vol %)	Oxidizing properties	
-	-	

#### Solubility

Solubility in water	n-octanol/water coefficient
Insoluble	-

### 9.2. Other information

Solubility in fat	Additional information
-	N/A

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available

### 10.2. Chemical stability

The product is stable under the conditions, noted in the section on "Handling and storage".

### 10.3. Possibility of hazardous reactions

No special

### 10.4. Conditions to avoid

Avoid static electricity. Do not expose to heat (e.g. sunlight), because it can lead to excess pressure.

### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidising agents, and strong catabolic agents.

### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Substance	Species	Test	Route of exposure	Result
No data available.				

#### Skin corrosion/irritation

No data available.

#### Serious eye damage/irritation

No data available.

#### Respiratory or skin sensitisation

No data available.

#### Germ cell mutagenicity

No data available.

#### Carcinogenicity

No data available.

#### Reproductive toxicity

No data available.

#### STOT-single exposure

No data available.

#### STOT-repeated exposure

No data available.

#### Aspiration hazard

No data available.

#### Long term effects

Reproductive toxicity: This product contains teratogenic substances which can do long-term damage to human offspring. The effects on the child can be: death, deformity, delayed development, and functional disorders.

Reproductive toxicity: This product contains substances which can do damage to reproductive capacity, e.g. damage to germ cells or hormonal regulation. The effects can be: sterility, reduced fertility, menstruation disorders, etc.

Neurotoxic effect: This product contains organic solvents, which can have an effect on the nervous system. Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc.

Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will then be more prone to absorb dangerous substances, e.g. allergens.

Sensitivity effects: This product contains substances which can give an allergic reaction on contact with skin. The allergic reaction will typically set in 12-72 hours after exposure as the substance penetrates the skin and reacts with proteins in the outer skin. The body's immune system sees the chemically changed protein as a foreign body and will try to destroy it.

## SECTION 12: Ecological information

### 12.1. Toxicity

Substance	Species	Test	Test duration	Result
No data available.				

### 12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
No data available.			

### 12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BFC
No data available.			

### 12.4. Mobility in soil

No data available

### 12.5. Results of PBT and vPvB assessment

No data available

### 12.6. Other adverse effects

This product contains ecotoxic substances which can have damaging effects on water-organisms. This product contains substances which can cause undesirable long-term effects in the water environment, due to its poor biodegradability.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

The product is covered by the regulations on dangerous waste.

#### Waste

EWC code

-

#### Specific labelling

-

#### Contaminated packing

Packaging which contains leftovers from the product must be disposed of in the same way as the product.

## SECTION 14: Transport information

This product is covered by the conventions on dangerous goods.

### 14.1 – 14.4

ADR/RID	14.1. UN number	14.2. UN proper shipping name	14.3. Transport hazard class(es)		14.4. Packing group		Notes
	1263		3		III		-
IMDG	UN-no.	Proper Shipping Name	Class	PG*	EmS	MP**	Hazardous constituent
	1263	Paint	3	III	-	-	-

### 14.5. Environmental hazards

-

### 14.6. Special precautions for user

-

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available

(\*) Packing group

(\*\*) Marine pollutant

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions for application

People under the age of 18 must not be exposed to this product cf. Council Directive 94/33/EC. For exceptions, see the Danish Working Environment Authority's Executive Order No. 239 of 6 April 2005.

#### Demands for specific education

-

#### Additional information

-

## 15.2. Chemical safety assessment

No

### SECTION 16: Other information'

#### Sources

EC regulation 1907/2006 (REACH)  
Directive 2000/532/EC  
EC Regulation 1272/2008 (CLP)

#### Full text of H/R-phrases as mentioned in section 3

R10 - Flammable.  
R43 - May cause sensitisation by skin contact.  
R62 - Possible risk of impaired fertility.  
R65 - Harmful: may cause lung damage if swallowed.  
R66 - Repeated exposure may cause skin dryness or cracking.  
R67 - Vapours may cause drowsiness and dizziness.  
R20/21/22 - Harmful by inhalation, in contact with skin and if swallowed.  
R36/38 - Irritating to eyes and skin.  
R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
H226 - Flammable liquid and vapour.  
H302 - Harmful if swallowed.  
H304 - May be fatal if swallowed and enters airways.  
H312 - Harmful in contact with skin.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H332 - Harmful if inhaled.  
H336 - May cause drowsiness or dizziness.  
H361 - Suspected of damaging fertility or the unborn child.  
H400 - Very toxic to aquatic life.  
H410 - Very toxic to aquatic life with long lasting effects.  
EUH066 - Repeated exposure may cause skin dryness or cracking.

#### The full text of identified uses as mentioned in section 1

#### Other symbols mentioned in section 2

-

#### Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version)) is marked with a blue triangle.

#### The safety data sheet is validated by

LFH

#### Date of last essential change (First cipher in SDS version)

-

#### Date of last minor change (Last cipher in SDS version)

-