

Safety data sheet

Solvent

1. Identification of the substance/preparation and of the company/undertaking

Prepared on: 04-03-2010/ LFH Distributor:

Replaces: 09-04-2008 WoodCare Denmark A/S

Tværvei 6

Product use: For thinning of oils and cleaning of tools 6640 Lunderskov

Tel:99585600 Fax:99585634

Emergency telephone number: 99585600

The emergency telephone is open between 8 a.m. and 4

p.m. on workdays.

Contact person:Environmental Department

Email: info@ttwoodcare

2. Hazards identification

DSD/DPD-classification

Xn

Harmful: May cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

Additional information

Risk of self-ignition: Due to the risk of self- ignition it is important that sanding dust and oil wetted cloths are soaked in water and disposed of in a tightly closed container after use

3. Composition/information on ingredients

Einecs no.	CAS No.	Substances	DSD-Classification	w/w%	
265-149-8	64742-47-8	Alkane, Iso	Xn;R65-66	100	
Please see se	ection 16 for the fu	Ill text of the R-phrases			

4. First aid measures

Inhalation

Seek fresh air.

Ingestion

Seek medical advice immediately. Do not induce vomiting. If vomiting occurs, keep head low so that stomach contents do not enter lungs.

Skir

Wash skin with water and soap. Seek medical advice in case of persistent discomfort.

Eves

Rinse immediately with water (preferably using eye wash) for at least 5 minutes. Open eyes wide. Remove any contact lenses.

Other information

When obtaining medical advice, show the safety data sheet or label. Symptoms: See section 11.

5. Fire-fighting measures

Extinguish with powder, foam, carbon dioxide or water mist. Do not use water stream, as it may spread the fire. Use water or water mist to cool non-ignited stock. Move containers from danger area if it can be done without risk. Avoid inhalation of vapour and flue gases – seek fresh air.

6. Accidental release measures

Use the same personal protective equipment as stated in section 8.

WoodCare Denmark A/S Tværvej 6, 6640 Lunderskov Tlf.: 99585600 Fax: 99585634, www.woodcaredenmark.com

Prepared on: 04-03-2010/LFH Solvent

Replaces: 09-04-2008

7. Handling and storage

Handling

Smoking and naked flames prohibited. See section 8 for information about precautions for use and personal protective equipment.

Storage

Store safely, out of reach of children and not together with food, animal feeding stuffs, medicines, etc.

Do not expose to heat (e.g. sunlight). Store frost-free. Keep in tightly closed original packaging.

8. Exposure controls/ personal protection

Precautions for use

Use the product under well-ventilated conditions.

Respiratory protection

Not required.

Gloves and protective clothing

Wear protective gloves made of nitrile rubber,

Eve protection

Wear safety goggles if there is a risk of eye splash.

Occupational exposure limits

Contains no substances subject to reporting requirements.

9. Physical and chemical properties

Appearance: Liquid

Boiling point: - °C >250 Density: - g/mL 0,8 Flash point: - °C >100

10. Stability and reactivity

The product is stable when used in accordance with the supplier's directions.

11. Toxicological information

Acute

Inhalation

Inhalation of vapours may cause irritation to the upper airways.

Ingestion

May cause chemical pneumonia if ingested or vomited.

Skin contact

Repeated exposure may cause skin dryness or cracking.

Eye contact

May cause eye irritation.

Long-term effects

None known.

12. Ecological information

Avoid discharge to drain or surface water.

WoodCare Denmark A/S Tværvej 6, 6640 Lunderskov Tlf.: 99585600 Fax: 99585634, www.woodcaredenmark.com

13. Disposal considerations

Contact the local authorities.

14. Transport information

The product is not covered by the rules for transport of dangerous goods by road and sea according to ADR and IMDG.

15. Regulatory information



Hazard designation: Harmful

Hazard symbols: Xn

Contains Alkane, Iso

R-phrases

Harmful: May cause lung damage if swallowed. (R65)

Repeated exposure may cause skin dryness or cracking. (R66)

S-phrases

Keep out of the reach of children. (S2)

If swallowed, do not induce vomiting, seek medical advice immediately and show this container or label. (S62)

If swallowed seek medical advice immediately and show this container or label. (S46)

Other labelling

Risk of self-ignition: Due to the risk of self- ignition it is important that sanding dust and oil wetted cloths are soaked in water and disposed of in a tightly closed container after use

Volatile organic compounds (VOC):

This product contains a maximum of 5 g VOC/L.

Chemical safety assessment

Chemical safety assessment has not been performed.

16. Other information

Restrictions on use

Training requirement

No special training is required, but a thorough knowledge of this safety data sheet should be a prerequisite condition.

Sources used

Approved classification and labelling guide (fifth edition) 2002.

Approved Supply List (seventh edition): Information approved for the classification and labelling of substances and preparations dangerous for supply. Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

Other information

This safety data sheet was prepared from information provided by the supplier about physical/chemical properties and all ingredients in the product.

Full text of the R-phrases that are stated in section 3.

R65 Harmful: May cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

WoodCare Denmark A/S Tværvej 6, 6640 Lunderskov Tlf.: 99585600 Fax: 99585634, www.woodcaredenmark.com (Made in Toxido®) UK